



## **CMM AutoQAL**

Gasmeter CMM AutoQAL is a fully automated EN 15267 certified solution for continuous mercury monitoring including automatic QAL3 validation tool for  $\text{HgCl}_2$  span check according to EN14181

MCERTS pending

## System specifications

<b>Measuring principle</b>	Cold vapor atomic fluorescence (CVAf) with extractive filtration, dilution and thermal conversion
<b>Measuring range</b>	Minimum certified range 0 - 5 µg/m <sup>3</sup> Maximum certified range 0 - 1000 µg/m <sup>3</sup>
<b>Detection limit</b>	0.02 µg/m <sup>3</sup> , total Hg with complete system
<b>Power supply</b>	Standard version: 400 VAC, 3 x L+N+PE 3 x 16 A (2 - 14 m sample line) 3 x 32 A (15 - 30 m sample line) Power consumption ~ 8kW with 25 m line  US version: 200 VAC, 3 x L+N+PE
<b>Response time</b>	Typically < 120 s
<b>Drift</b>	< 2 % of measuring range per 24 hours calibration interval (zero point, span calibration and linearity)
<b>Sampling probe</b>	Heated probe with particle filter, flow monitoring and sample dilution
<b>Test Gas Generator for Hg<sup>0</sup></b>	Vapor generation from saturated source and dilution Zero-point calibration interval: 24 hours (adjustable) Hg <sup>0</sup> -span calibration interval: 24 hours (adjustable)
<b>QAL3 validation tool</b>	Automatic HgCl <sub>2</sub> test gas generator. Validation interval 4 weeks.
<b>Heated sample line length</b>	Standard 230 V version: 2 - 35 m (according to site) US 115 V version: 2 - 14 m (according to site)
<b>Input signals</b>	External standby control
<b>Output signals</b>	5 device status contacts: System alarm, service request, maintenance status, result valid and concentration alarm 4 analog signals (4 - 20 mA) for measurement data
<b>Enclosure</b>	<b>Dimensions (H x W x D):</b> Control unit 212 x 61 x 70 cm (cooling unit on top) <b>Material:</b> Bake painted steel <b>IP class:</b> IP54
<b>Weight</b>	Sampling probe approximately 27 kg Cabinet approximately 230 kg

---

## Sample gas conditions

---

<b>Sample gas temperature</b>	Up to 400 °C (max in stack)
<b>Sample gas pressure</b>	0.9 – 1.2 bars (in stack)
<b>Sample gas dust content</b>	0 – 2g/m <sup>3</sup>

---

## Operating conditions

---

<b>Control unit ambient temperature</b>	5 – 40 °C
<b>Sampling probe ambient temperature</b>	-20 – 50 °C
<b>Instrument air requirements</b>	<b>Quality</b> 6 - 10 bar, oil free, dew point < -5 °C
	<b>Consumption</b> 60 l/min

Gasmeter Technologies Oy shall not be liable for technical or editorial errors or omissions contained herein. The information in this document is provided "as is" without warranty of any kind and is subject to change without notice. Should you find any errors, we would appreciate if you notified us.